



Simplex Manufacturing dba Simplex Aerospace
13340 NE Whitaker Way Portland, OR 97230
mail@simplexmfg.com www.simplex.aero
Main Phone (503) 257-3511 Fax (503) 257-8556



Simplex Model 308 Fire Attack System

Bell 407





Simplex Model 308 Fire Attack System

Bell 407





Simplex Manufacturing dba Simplex Aerospace
 13340 NE Whitaker Way Portland, OR 97230
 mail@simplexmfg.com www.simplex.aero
 Main Phone (503) 257-3511 Fax (503) 257-8556

Simplex Model 308 ▪ Fire Attack System

Bell 407

Certifications	
FAA STC #SR00769SE	Bell 407
Argentina ANAC #LV-BBP	Bell 407
Mexico DGAC #IA-450/2017	Bell 407

Features & Benefits	Installation Requirements
FAA certified for day/night VFR operations Installation/removal in 30 minutes	Approved cargo hook mirror Approved standard high skid gear

The Simplex Model 308 FAS can be installed on the Bell 407 with AA or Bell skid gear.

FAS Details	
Tank Weight	287 lb / 130 kg
System Capacity	245 gal / 927 L
Foam Capacity	7.5 gal / 28 L
Hover Refill Rate	280 GPM / 1060 LPM
Vne (Hover Pump Installed)	120 KIAS
Vne (Hover Pump Removed)	120 KIAS

Simplex Sales		
Michael Finnegan Director of Business Development Asia mfinnegan@simplexmfg.com	Casey Zimmerman Director of Product Sales North/South America, Australia, and New Zealand czimmerman@simplexmfg.com	Ian Cockburn Regional Sales Manager Europe, Africa, Russia, and Middle East ian@simplexmfg.com

