



Simplex Manufacturing dba Simplex Aerospace
13340 NE Whitaker Way Portland, OR 97230
mail@simplexmf.com www.simplex.aero
Main Phone (503) 257-3511 Fax (503) 257-8556



Simplex Model 326 GII Fire Attack System

AgustaWestland AW139





Simplex Model 326 GII Fire Attack System

AgustaWestland AW139





Simplex Manufacturing dba Simplex Aerospace
 13340 NE Whitaker Way Portland, OR 97230
 mail@simplexmfg.com www.simplex.aero
 Main Phone (503) 257-3511 Fax (503) 257-8556

Simplex Model 326 GII • Fire Attack System

AgustaWestland AW139

C e r t i f i c a t i o n s	
FAA STC #SR02351LA	AW-139
Japan JCAB #STC-382-2-TYO	AW-139
EASA #10058981 (Aux. Quick Step not approved)	AW-139

I n s t a l l a t i o n R e q u i r e m e n t s	
<ul style="list-style-type: none"> • Configured for firefighting operations with Agusta Kit 4G2590F00513, 4A2590F00513 or AG2590F00514 • Agusta Kit number 4G0000F00111, 6800 kg gross weight increase, recommended • Agusta landing gear lockout kit 	<ul style="list-style-type: none"> • Hoist search light removed and blanking plate installed • Flotation system must be inactive • Cargo hook cameras removed and blanking plate installed • Aft passenger steps must be removed


F A A c e r t i f i e d f o r d a y / n i g h t V F R o p e r a t i o n s
 I n s t a l l a t i o n / r e m o v a l i n 3 0 m i n u t e s

F A S D e t a i l s	
Tank Weight (not including Hover Pump)	498 lb / 226 kg
System Capacity	480 gal / 1817 L
Optional Foam Tank Assembly Capacity	25 gal / 95 L
Hover Refill Rate	400 GPM / 1514 LPM
Vne (Hover Pump Installed)	140 KIAS
Vne (Hover Pump Removed)	150 KIAS



Simplex Model 326 GII • Fire Attack System

AgustaWestland AW139

Optional Quick Step	
<p>The Simplex Model 926 Quick Step allows for rapid transition between mission types</p> <p>FAA STC#SR02351LA</p>	
<p>Quick Step designed to be installed/removed in less than 2 minutes.</p> <p>Weight: 60 lb / 27 kg</p>	<p>Requires same provision kit as 326 GII.</p> <p>No additional installation requirements.</p>
	<ul style="list-style-type: none"> • Vertical profile in line with tank for safe and easy entry and exit from aircraft • Quick attach fittings allow operators a solution for fast response to changes in mission configuration requirements • Attaches to 326 GII system hardpoints

Simplex Sales		
<p>Michael Finnegan Director of Business Development Asia mfinnegan@simplexmfmg.com</p>	<p>Casey Zimmerman Director of Product Sales North/South America, Australia, and New Zealand czimmerman@simplexmfmg.com</p>	<p>Ian Cockburn Regional Sales Manager Europe, Africa, Russia, and Middle East ian@simplexmfmg.com</p>