



Simplex Manufacturing dba Simplex Aerospace
13340 NE Whitaker Way Portland, OR 97230
mail@simplexmf.com www.simplex.aero
Main Phone (503) 257-3511 Fax (503) 257-8556



Simplex Model 7900 Spray System

Bell 206 L Series





Simplex Model 7900 Spray System

Bell 206 L Series





Simplex Manufacturing dba Simplex Aerospace
 13340 NE Whitaker Way Portland, OR 97230
 mail@simplexmf.com www.simplex.aero
 Main Phone (503) 257-3511 Fax (503) 257-8556

Simplex Model 7900 ▪ Spray System

Bell 206 L Series

Certifications	
FAA STC #SH4377NM	206 L, L-1, L-3 L-4
Canada TC #SH90-22	206 L, L-1, L-3, L-4
China CAAC	Pending

Features & Benefits	
<p>Installation/removal in 30 minutes</p> <p>Flow controller allows operator to adjust chemical output.</p>	<p>Mid-ship mounted booms.</p> <p>Aerodynamic design results in low drag.</p> <p>Safety features include emergency jettison dump doors and pump stop controls.</p>

Spray System Details	
Tank Weight	225 lb / 102 kg
System Capacity	160 gal / 606 L
Boom Span (77% RD)	29 ft / 9 m
Boom Span (99% RD)	37 ft / 11 m
Estimated Swath Width	45-60 ft / 14-18 m
Nozzle Ports	52 (¼" NPT)
Vne (Outer Booms Installed)	100 MPH / 86.89 KIAS
Vne (Outer Booms Removed)	130 MPH / 112.96 KIAS





Simplex Manufacturing dba Simplex Aerospace
13340 NE Whitaker Way Portland, OR 97230
mail@simplexmfg.com www.simplex.aero
Main Phone (503) 257-3511 Fax (503) 257-8556

Simplex Model 7900 ▪ Spray System

Bell 206 L Series

Installation Requirements	Electrical Requirements
Approved standard high skid gear Bell Helicopter 2000 lb Cargo Hook Kit	Current: 90 Amps Voltage: 28 VDC Simplex 7600 Electrical System: Simplex P/N 000-007600-101 FAA STC #SH4173NM

Simplex Sales		
Michael Finnegan Director of Business Development Asia mfinnegan@simplexmfg.com	Casey Zimmerman Director of Product Sales North/South America, Australia, and New Zealand czimmerman@simplexmfg.com	Ian Cockburn Regional Sales Manager Europe, Africa, Russia, and Middle East ian@simplexmfg.com