



Simplex Manufacturing dba Simplex Aerospace
13340 NE Whitaker Way Portland, OR 97230
mail@simplexmfg.com www.simplex.aero
Main Phone (503) 257-3511 Fax (503) 257-8556

Simplex Model 8500 Spray System

Hughes 369 Series, MD 500 N





Simplex Manufacturing dba Simplex Aerospace
 13340 NE Whitaker Way Portland, OR 97230
 mail@simplexmfg.com www.simplex.aero
 Main Phone (503) 257-3511 Fax (503) 257-8556

Simplex Model 8500 ▪ Spray System

Hughes 369 Series, MD 500 N

Certifications	
FAA STC #SH7091NM	Hughes 369, A, H, HM, HS, HE, D, E, F, FF, 500 N
Canada TC #SH15-11	Hughes 369, A, H, HM, HS, HE, D, E, F, FF, 500 N

Features & Benefits	
<p>Installation/removal in 30 minutes</p> <p>Flow controller allows operator to adjust chemical output.</p>	<p>Mid-ship mounted booms.</p> <p>Aerodynamic design results in low drag.</p> <p>Safety features include emergency jettison dump doors and pump stop controls.</p>

Spray System Details	
Tank Weight	221 lb / 100 kg
System Capacity	130 gal / 492 L
Boom Span (66% RD)	27 ft / 8 m
Boom Span (75% RD)	35 ft / 11 m
Estimated Swath Width	50-70 ft / 15-21 M
Nozzle Ports	52 (¼" NPT)
Vne	100 KIAS

Installation Requirements	Electrical Requirements
<ul style="list-style-type: none"> Approved standard high skid gear 	<p>Current: 90 Amps</p> <p>Voltage: 28 VDC</p>

Simplex Sales		
<p>Michael Finnegan Director of Business Development Asia mfinnegan@simplexmfg.com</p>	<p>Casey Zimmerman Director of Product Sales North/South America, Australia, and New Zealand czimmerman@simplexmfg.com</p>	<p>Ian Cockburn Regional Sales Manager Europe, Africa, Russia, and Middle East ian@simplexmfg.com</p>

