



# **SIMPLEX Model 516**

## **for the EC225LP, H225**

### **SPECIFICATIONS**

Capacity	600 US gal	492 ltr
System Weight	1275 lb	578 kg
Foam Capacity	24 gal	91 ltr
Hover Refill Rate	1000 GPM	3785 LPM
Vne (Booms Stowed)	130 KIAS	
Vne (Booms Removed)	130 KIAS	

### **CERTIFICATIONS**

United States	FAA STC	SR02459SE
Japan	JCAB	STC-437-TYO

### ★ **FEATURES** ★

**40 Meters Effective Range**

**Installation/removal in 30 min**

**Day/Night VFR Approved**

**1 Year Warranty**

**24/7 Customer Service**

**150 PSI**

**200 GPM Output**

**Low Pressure, High Volume Spray**

*For more information, contact a representative:*

**Asia:** Michael Finnegan, [mfinnegan@simplexmfg.com](mailto:mfinnegan@simplexmfg.com)

**Europe · Russia · Middle East · Africa:** Ian Cockburn, [ian@simplexmfg.com](mailto:ian@simplexmfg.com)

**Americas · Australia · New Zealand:** Casey Zimmerman, [czimmerman@simplexmfg.com](mailto:czimmerman@simplexmfg.com)

